

DECLARATION OF PERFORMANCE

DoP No. 1343-CPR-M 510-3 - EN

1. Unique identification code of the product-type:

fischer Drop-in Anchor EA II

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

ETA-07/0142, Annex A1 – A3

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Generic type	Deformation controlled expansion anchor for multiple use for non-structural applications in concrete
For use in	Cracked and non-cracked concrete C20/25 – C50/60 (EN 206)
Loading	Static and quasi-static; Fire (EOTA TR020)
Material	Zinc-plated steel: Dry internal conditions only Covered sizes: M6x25, M6x30, M8x25, M8x30, M8x40, M10x25, M10x30, M10x40, M12x25, M12x50
	Stainless steel (marking A4): Internal and external use without particular aggressive conditions Covered sizes: M6x30, M8x30, M8x40, M10x30, M10x40, M12x50

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

fischerwerke GmbH & Co. KG, Klaus-Fischer-Straße 1, 72178 Waldachtal, Germany

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): ---

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **2+**

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard: ---

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

**Deutsches Institut für Bautechnik (DIBt) issued ETA-07/0142
on the basis of ETAG 001-6.**

MPA Darmstadt 1343-CPR performed

- (i) initial inspection of the manufacturing plant and of factory production control;
- (ii) continuous surveillance, assessment and evaluation of factory production control.

under system **2+** and the number of the certificate of constancy of performance is **1343-CPR-M 510-3**.

9. Declared performance

Essential characteristics	Design Method	Performance	Harmonised technical specification
Characteristic resistance for tension	ETAG 001 Annex C	ETA-07/0142, Annex C1	ETAG 001-6
Characteristic resistance for shear	ETAG 001 Annex C	ETA-07/0142, Annex C1	
Minimum spacing and minimum edge distance	ETAG 001 Annex C	ETA-07/0142, Annex B3	
Characteristic resistance to fire	EOTA TR 020	ETA-07/0142, Annex C3	EOTA TR 020 (informative)

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

i. V. W. Hengesbach

Wolfgang Hengesbach
Dipl.-Ing., Dipl.-Wirtsch.-Ing.
Zulassungen & Technische Dokumente

i. V. A. Bucher

Andreas Bucher
Dipl.-Ing.
Forschung & Technologietransfer



Waldachtal, 2014-11-14